




# ScenaticFlex 600 LED



**TRILUX**  
NEW LIGHT.



**ScenaticFlex 600 LED**

**A real eye-catcher with a clear focus.**

The ScenaticFlex 600 LED surface-mounted directional spotlight confidently sets room elements and details in focus, with ease due to its wide action radius. At the same time, newly developed reflector technology ensures pleasant, homogeneous light distribution. The UV and IR-free light is especially caring and ideal for the illumination of valuable goods.

**For setting in scene:** The adjustable luminaire enables a unique illumination of room elements and confidently emphasises details.

**Rapid:** Mounting in only one step thanks to a 3-circuit adapter.

**Simple:** The reflector can be replaced easily and completely without tools.

**Future-fit:** Increasing efficiency with future generation changes giving constant light output and constant light quality.

**Caring:** The UV and IR-free light is especially suitable for presenting high-value objects and goods, for example in museums and hotels.

The 3D faceted reflector can be replaced in only one step and completely without tools, thanks to familiar interchangeable reflector technology.

ScenaticFlex 600 LED is extremely flexible for the illumination of room elements. It can be rotated through 355° and is cardanically mounted on two axes.

The integral TRILUX LED technology is ideally suited to presenting high quality exponents, with caring IR and UV-free light serving to lengthen their life.



# ScenaticFlex 600 LED

## Surface-mounted directional spotlight

CE  IP20



LED surface-mounted spotlight for 3-circuit track, structure powder-coated, can be rotated through 355° and pivoted through  $\pm 60^\circ$ , with 1 LED array module.

...**ww**... Light colour warm white, colour temperature 3000 K, luminous flux 2300 lm

...**nw**... Light colour neutral white, colour temperature 4000 K, luminous flux 2700 lm.


LED with constant colour stability and a colour rendering index of  $R_a > 80$  for the complete service life. Pivotable reflector housing of sheet steel, asymmetrically integrated in rotatable rectangular control gear housing for the control unit. Control gear housing of sheet steel, thermally separated and symmetrically positioned with offset lateral applications of sheet steel in deep black, similar to RAL 9005. Glare-reduced 3D reflector of aluminium, faceted, integrated in reflector housing. Front ring with bayonet fixing mechanism enables replacing of reflector unit. Spotlight complete with 3-circuit track adapter. With electronic transformer.

...**01** White, similar to RAL 9016, white 3-circuit adapter.


...**03** Silver-grey, similar to RAL 9006, black 3-circuit adapter.

...**SP**... Spot distribution characteristic.

...**MF**... Medium distribution characteristic.



**SncFlex 600 BR-MF LED 2700 nw**...  
 UTE: 1.00 A + 0.00 T  
 DIN 5040: A80  
 CIBSE: BZ 1  
 NBN L 14-002: BZ 1




**SncFlex 600 BR-SP LED 2300 ww**...  
 UTE: 1.00 A + 0.00 T  
 DIN 5040: A80  
 CIBSE: BZ 1  
 NBN L 14-002: BZ 1

Designation	TOC	Electrical version ...ET...	Colour	Lamps/ luminous flux/ light colour	Connected load	≈kg
SncFlex 600 BR-MF LED 2300 ww...03	60 367...	...40	silver/black	LED/2300 lm/ww	41	2.6
SncFlex 600 BR-SP LED 2300 ww...03	60 369...	...40	silver/black	LED/2300 lm/ww	41	2.6
SncFlex 600 BR-MF LED 2700 nw...03	60 368...	...40	silver/black	LED/2700 lm/nw	41	2.6
SncFlex 600 BR-SP LED 2700 nw...03	60 370...	...40	silver/black	LED/2700 lm/nw	41	2.6
SncFlex 600 BR-MF LED 2300 ww...01	60 339...	...40	white/black	LED/2300 lm/ww	41	2.6
SncFlex 600 BR-SP LED 2300 ww...01	60 340...	...40	white/black	LED/2300 lm/ww	41	2.6
SncFlex 600 BR-MF LED 2700 nw...01	60 341...	...40	white/black	LED/2700 lm/nw	41	2.6
SncFlex 600 BR-SP LED 2700 nw...01	60 342...	...40	white/black	LED/2700 lm/nw	41	2.6

Accessories	TOC	Ø mm	Description
Snc ZBR-G 105 MF LED	60 361 00	105	Reflector, gold
Snc ZBR-G 105 SP LED	60 362 00	105	Reflector, gold
Snc ZBR-G 105 FL LED	60 363 00	105	Reflector, gold
Snc ZBR-S 105 MF LED	60 364 00	105	Reflector, silver
Snc ZBR-S 105 SP LED	60 365 00	105	Reflector, silver
Snc ZBR-S 105 FL LED	60 366 00	105	Reflector, silver

SncFlex 600...LED...



## Contacts

### **TRILUX GmbH & Co. KG**

Heidestraße · D-59759 Arnsberg  
Postfach 19 60 · D-59753 Arnsberg  
Tel. +49 (0) 29 32.3 01-0  
Fax +49 (0) 29 32.3 01-3 75  
sales@trilux.com · www.trilux.com

### **TRILUX LIGHTING LIMITED**

TRILUX HOUSE, Winsford Way  
Boreham Interchange  
Chelmsford, Essex  
CM2 5PD  
Tel. +44 (0) 12 45.46 34 63  
Fax +44 (0) 12 45.46 26 46  
sales@trilux.co.uk · www.trilux.co.uk

### **PROLJUS AB**

Kyrkogatan 18  
570 03 VRIGSTAD  
Tel. +46 (0) 70 601 05 63  
info@proljus.se - www.proljus.se





